



ŠKODA
SIMPLY CLEVER

ŠKODA CITIGO

Petrol engines

Technical specifications	1.0 MPI/44 kW	1.0 MPI/44 kW (A)	1.0 MPI/50 kW G-TEC	1.0 MPI/55 kW	1.0 MPI/55 kW (A)
Engine					
Engine type	petrol engine, in-line, liquid cooling system, DOHC, transverse in front				
Cylinders	3				
Displacement [cm ³]	999				
Bore x Stroke [mm x mm]	74.5 x 76.4				
Max. engine performance/revs [kW at rpm]	44/5000		50/6200		55/6200
Max. torque/revs [Nm at rpm]	95/3000		90/3000		95/3000
Compression ratio	10.5 : 1		11.5 : 1		10.5 : 1
Emission limit	EU 6				
Fuel injection system	electronic multipoint fuel injection MPI				
Ignition	control unit controlled electronic ignition system				
Lubrication	force-feed lubrication with through-flow oil filter				
Fuel quality	unleaded petrol min. RON 95 (91)*		unleaded petrol min. RON 95; natural gas – CNG	unleaded petrol min. RON 95 (91)*	
Transmission					
Wheel drive	front wheel drive				
Clutch	hydraulic single dry clutch disc with membrane spring, asbestos free	controlled by electromechanical elements, single dry clutch disc with membrane spring, asbestos free	hydraulic single dry clutch disc with membrane spring, asbestos free		controlled by electromechanical elements, single dry clutch disc with membrane spring, asbestos free
Transmission	manual 5-speed fully synchronized	automatic 5-speed, ASG, with manual gear changing	manual 5-speed fully synchronized		automatic 5-speed, ASG, with manual gear changing
Transmission ratio	I-3.64 II-1.96 III-1.21 IV-0.92 V-0.76 R-3.62	I-3.64 II-2.14 III-1.36 IV-0.96 V-0.80 R-3.62	I-3.64 II-1.96 III-1.27 IV-0.96 V-0.80 R-3.62	I-3.64 II-1.96 III-1.21 IV-0.92 V-0.76 R-3.62	I-3.64 II-2.14 III-1.36 IV-0.96 V-0.80 R-3.62
Axle ratio	3.895		4.167	3.895	4.167



ŠKODA
SIMPLY CLEVER

ŠKODA CITIGO

Petrol engines

Technical specifications	1.0 MPI/44 kW	1.0 MPI/44 kW (A)	1.0 MPI/50 kW G-TEC	1.0 MPI/55 kW	1.0 MPI/55 kW (A)
Chassis					
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser				
Rear axle	compound link crank-axle				
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs				
Braking system	hydraulic dual-diagonal circuit braking system vacuum assisted with Dual Rate system				
Brake – front	disc brakes with inner cooling, with single/piston floating caliper				
Brake – rear	drum brakes				
Parking brake	manual, on rear wheels				
Steering system	direct rack and pinion steering with electrohydraulic power steering				
Wheels	5J x 14"				
Tyres	165/70 R14 [175/65 R14]		175/65 R14		165/70 R14 [175/65 R14]
Body					
Body	3-door {5-door}, two compartment, 4 seater				
Drag coefficient c_w	0.320 [0.315]		0.325		0.320 [0.315]
Outside dimensions					
Length [mm]	3597				
Width [mm]	1641 {1645}				
Height (at kerb weight) [mm]	1478 [1463]		1480		1478 [1463]
Wheel base [mm]	2420		2421		2420
Clearance (at kerb weight) [mm]	136 [121]		134		136 [121]
Height of the loading sill (at kerb weight) [mm]	769 [753]		773		769 [753]
Track front [mm]	1428				
Track rear [mm]	1424				
Inside dimensions					
Width of front seats [mm]	1417 {1369}				
Width of rear seats [mm]	1389 {1388}				
Headroom in front seats [mm]	993				
Headroom in rear seats [mm]	947				
Storage capacity [l]	251		213		251
Storage capacity – with rear seatback folded down [l]	951 {959}		913 {921}		951 {959}



ŠKODA
SIMPLY CLEVER

ŠKODA CITIGO

Petrol engines

Technical specifications		1.0 MPI/44 kW	1.0 MPI/44 kW (A)	1.0 MPI/50 kW G-TEC	1.0 MPI/55 kW	1.0 MPI/55 kW (A)
Weights						
Kerb weight – incl. driver**	[kg]	929 [940]	932 [931]	1031	929 [940]	932 [931]
Payload – incl. driver**	[kg]	436 [425]	433 [444]	414	436 [425]	433 [444]
Total weight	[kg]	1290	1290 [1300]	1370	1290	1290 [1300]
Liquids						
Tank capacity	[l]	35		petrol: 10; CNG: 11 kg	35	
Performance/consumption						
Maximum speed	[km/h]	162	162	165	173	173
Acceleration 0–100 km/h	[s]	14.4	16.7	16.3	13.5	14.9
Fuel consumption (1999/100/EC)						
Consumption – urban	[l/100 km]	5.5 [4.9]	5.3 [4.7]	5.6 m ³ /100 km	5.4 [4.9]	5.3 [4.9]
Consumption – extra-urban	[l/100 km]	3.8 [3.7]	3.8 [3.7]	3.9 m ³ /100 km	3.8 [3.7]	3.9 [3.8]
Consumption – combined	[l/100 km]	4.4 [4.1]	4.3 [4.1]	4.5 m ³ /100 km	4.4 [4.1]	4.4 [4.2]
CO ₂ emissions	[g/km]	101 [96]	100 [95]	82	101 [96]	103 [97]
Turning circle diameter	[m]	9.8				

The technical data is valid for the basic version.

Specifications are preliminary.

* Using low-octane fuel may affect engine performance.

** Figures apply to basic version, weight of driver 75 kg.

[] Applies to Green tec.

{ } Applies to 5-door version.