



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA KAROQ SCOUT

## Diesel engines

Technical specifications	2.0 TDI/110 kW 4×4 (A)
<b>Engine</b>	
Engine type	turbocharged diesel engine, turbocharger with self-aligning blades, in-line, liquid cooling system, DOHC, transverse in front
Cylinders	4
Displacement [cm <sup>3</sup> ]	1968
Bore × Stroke [mm × mm]	81.0 × 95.5
Max. engine performance/revs [kW at rpm]	110/3500–4000
Max. torque/revs [Nm at rpm]	340/1750–3000
Compression ratio	16.2 : 1
Emission limit	EU 6 DG
Fuel injection system	electronically controlled high-pressure direct injection – common-rail system
Lubrication	force-feed lubrication with through-flow oil filter
Fuel quality	diesel
<b>Transmission</b>	
Wheel drive	four-wheel drive with automatic torque distribution
Clutch	two coaxial wet multiple-disk clutch, electro-hydraulically operated
Transmission	automatic 7-speed, DSG, with Tiptronic manual gear changing
Transmission ratio	I-3.579 II-2.750 III-1.677 IV-0.889 V-0.677 VI-0.722 VII-0.561 R-2.900
Axle ratio	I-4.471 II-3.304
<b>Chassis</b>	
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs
Braking system	hydraulic diagonal dual-circuit braking system, vacuum servo assisted
Brake – front	disc brakes with inner cooling, with single/piston floating caliper
Brake – rear	disc brakes
Parking brake	electromechanical, on rear wheels
Steering system	electromechanical power steering with variable ratio
<b>Body</b>	
Body	5 door, two compartment, 5 seater
Drag coefficient c <sub>w</sub>	0.342



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA KAROQ SCOUT

Diesel engines

Technical specifications		2.0 TDI/110 kW 4x4 (A)
Outside dimensions		
Length	[mm]	4399
Width	[mm]	1841
Height (at kerb weight)	[mm]	1626
Wheel base	[mm]	2630
Clearance (at kerb weight)	[mm]	183
Height of the loading sill (at kerb weight)	[mm]	684
Track front	[mm]	1572
Track rear	[mm]	1544
Inside dimensions		
Width of front seats	[mm]	1486
Width of rear seats	[mm]	1445
Headroom in front seats	[mm]	1058
Headroom in rear seats	[mm]	1020 – standard seats 993 – VarioFlex
Storage capacity	[l]	521 – standard seats 588*** – VarioFlex
Storage capacity with rear seats backrests down	[l]	1630 – standard seats 1605 – VarioFlex
Storage capacity with rear seats removed	[l]	1810 – VarioFlex
Weights		
Kerb weight – incl. driver**	[kg]	1591–1820
Payload – incl. driver**	[kg]	385–674
Total weight	[kg]	2141–2240
Max. roof load	[kg]	75
Max. trailer load w/o brakes	[kg]	750
Max. trailer load with brakes – 12%	[kg]	2100
Max. trailer load with brakes – 8%	[kg]	2100
Max. nose weight	[kg]	90
Liquids		
Tank capacity	[l]	55



**ŠKODA**  
SIMPLY CLEVER

# ŠKODA KAROQ SCOUT

## Diesel engines

Technical specifications		2.0 TDI/110 kW 4x4 (A)
Performance/consumption		
Maximum speed	[km/h]	193
Acceleration 0–100 km/h	[s]	9.2
Fuel consumption (NEDC)		
– urban	[l/100 km]	6.2
– extra-urban	[l/100 km]	4.9
– combined	[l/100 km]	5.4
CO <sub>2</sub> emissions	[g/km]	142
Fuel consumption (WLTP)		
– combined	[l/100 km]	6.0–6.9
CO <sub>2</sub> emissions	[g/km]	158–180
Turning circle diameter	[m]	10.2

The technical data is valid for the basic version.

\*\* Figures apply to basic version, weight of driver 75 kg.

\*\*\* The capacity depends on the position of the backrests and rear seats.

The specified fuel consumption and emission data have been determined according to the measurement procedures prescribed by law. Since 1st September 2017, certain new vehicles are already being type-approved according to the Worldwide Harmonized Light Vehicles Test Procedure (WLTP), a more realistic test procedure for measuring fuel consumption and CO<sub>2</sub> emissions. Starting on September 1st 2018, the New European Driving Cycle (NEDC) will be replaced by the WLTP in stages. Owing to the more realistic test conditions, the fuel consumption and CO<sub>2</sub> emissions measured according to the WLTP will, in many cases, be higher than those measured according to the NEDC.

We are currently still required by law to state the NEDC figures. In the case of new vehicles which have been type-approved according to the WLTP, the NEDC figures are derived from the WLTP data. It is possible to specify the WLTP figures voluntarily in addition until such time as this is required by law. In cases where the NEDC figures are specified as value ranges, these do not refer to a particular individual vehicle and do not constitute part of the sales offering. They are intended exclusively as a means of comparison between different vehicle types. Additional equipment and accessories (e.g. add-on parts, different tyre formats, etc.) may change the relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, in conjunction with weather and traffic conditions and individual driving style, may affect fuel consumption, electrical power consumption, CO<sub>2</sub> emissions and the performance figures for the vehicle.