

Technical specifications		ENYAQ iV 60	ENYAQ iV 80	ENYAQ iV 80x	
Engine					
Engine type		permanent magnet synchronous motor			
Max. system engine performance	[kW]	132	150	195	
Max. torque	[Nm]	310		425	
Battery capacity brutto (netto)	[kWh]	62 (58)	82 (77)	82 (77)	
Battery type		Li-Ion (DC-high-voltage)			
Transmission					
Wheel drive		rear wheel drive		four-wheel drive	
Transmission		single-speed			
Axle ratio		4.389		3.900 / 2.760	
Chassis					
Front axle		MacPherson suspension with lower triangular links and torsion stabiliser			
Rear axle		multi-element axle, with five transverse links and torsion stabiliser			
Springs		telescopic shock absorbers with coil springs, in the rear outside the springs			
Braking system		hydraulic diagonal dual-circuit braking system, electromechanical servo assisted			
Brake – front		disc brakes with inner cooling, with single- piston floating caliper	disc brakes with inner cooling, with two-piston floating caliper		
Brake – rear		drum brakes			
Parking brake		electromechanical, on rear wheels			
Steering system		direct rack and pinion steering with electro mechanic power steering			
Body					
Body		5 door, two compartment, 5 seater			
Drag coefficient c _w		0.255-0.277	0.258-0.280	0.258-0.280	



Technical specifications		ENYAQ iV 60	ENYAQ iV 80	ENYAQ iV 80x	
Outside dimensions		ENTAGIV 00	LITTAG IV 00	ENTAGIV OUX	
Length	[mm]	4653			
Width	[mm]	1879			
Height (at kerb weight)	[mm]	1606 1604			
Wheel base	[mm]	2767 2768			
Clearance (at kerb weight)	[mm]	173			
Height of the loading sill (at kerb weight)	[mm]	688			
Track front	[mm]	1589			
Track rear	[mm]	1567			
Inside dimensions	[IIIII]		1307		
Width of front seats	[mm]	1506			
Width of rear seats	[mm]	1488			
Headroom in front seats	[mm]	1056			
Headroom in rear seats	[mm]				
Storage capacity	[1]	585			
Storage capacity – with rear seatback	ניו	303			
folded down	[1]	1710			
Weights					
Kerb weight – incl. driver*	[kg]	1992–2179	2107–2308	2195–2380	
Payload – incl. driver*	[kg]	396–583	416–575	445–630	
Total weight	[kg]	2500	2540–2649	2750	
Max. roof load	[kg]	75			
Max. trailer load w/o brakes	[kg]				
Max. trailer load with brakes – 12%	[kg]			1200	
Max. trailer load with brakes – 8%	[kg]			1400	
Max. nose weight	[kg]				



Technical specifications		ENYAQ iV 60	ENYAQ iV 80	ENYAQ iV 80x
Performance/consumption				
Maximum speed	[km/h]		160	
Acceleration 0–100 km/h	[s]	8.8	8.7	6.9
Fuel consumption (NEDC)				
- combined	[kWh/100 km]	14.4–15.9	15.8	16.0
CO ₂ emissions	[g/km]		0	
Turning circle diameter	[m]	9.3		10.8

The technical data is valid for the basic version.

The specified fuel consumption and emission data have been determined according to the measurement procedures prescribed by law. Since 1st September 2017, certain new vehicles are already being type-approved according to the Worldwide Harmonized Light Vehicles Test Procedure (WLTP), a more realistic test procedure for measuring fuel consumption and CO₂ emissions. Starting on September 1st 2018, the New European Driving Cycle (NEDC) will be replaced by the WLTP in stages. Owing to the more realistic test conditions, the fuel consumption and CO₂ emissions measured according to the WLTP will, in many cases, be higher than those measured according to the NEDC.

We are currently still required by law to state the NEDC figures. In the case of new vehicles which have been type-approved according to the WLTP, the NEDC figures are derived from the WLTP data. It is possible to specify the WLTP figures voluntarily in addition until such time as this is required by law. In cases where the NEDC figures are specified as value ranges, these do not refer to a particular individual vehicle and do not constitute part of the sales offering. They are intended exclusively as a means of comparison between different vehicle types. Additional equipment and accessories (e.g. add-on parts, different tyre formats, etc.) may change the relevant vehicle parameters, such as weight, rolling resistance and aerodynamics, and, in conjunction with weather and traffic conditions and individual driving style, may affect fuel consumption, electrical power consumption, CO₂ emissions and the performance figures for the vehicle.

^{*} Figures apply to basic version, weight of driver 75 kg.







