Superb Combi iV Petrol engine



Technical specifications	1.5 TSI/150 kW PHEV (A)
Engine	
Engine type	turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front and electromotor
Cylinders	4
Displacement [cm	3] 1498
Bore × Stroke [mm × mr	74.5 × 85.9
Max. engine performance/revs [kW/min	110/5500–6000
Max. torque/revs [Nm/min	250/1500–4000
Maximum output of electromotor [kV	/] 85
Maximum torque of electromotor [Nr	330
Maximum system output [kV	/]
Maximum system torque [Nr	350
Compression ratio	11.5 : 1
Emission limit	EU 6 EA
Fuel injection system	electronically controlled direct injection
Ignition	control unit controlled electronic ignition system
Lubrication	force-feed lubrication with through-flow oil filter
Fuel quality	unleaded petrol min. RON 95
Transmission	
Wheel drive	front wheel drive
Clutch	three coaxial wet multiple-disk clutch, electro-hydraulically operated
Transmission	automatic 6-speed, DSG, with Tiptronic manual gear changing
Transmission ratio	I-3.500 II-2.773 III-1.852 IV-1.020V-1.023 VI-0.840 R-2.864
Axle ratio	I-3.750 II-2.885
Chassis	
Front axle	MacPherson suspension with lower triangular links and torsion stabiliser
Rear axle	multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser
Springs	telescopic shock absorbers with coil springs, in the rear outside the springs
Braking system	hydraulic diagonal dual-circuit braking system, electromechanical servo assisted
Brake – front	disc brakes with inner cooling, with single/piston floating caliper
Brake – rear	disc brakes
Parking brake	electromechanical, on rear wheels
Steering system	direct rack and pinion steering with electro mechanic power steering

1/3 11. 3. 2024

Superb Combi iV Petrol engine



Tashuisalanasifisationa		A E TOUASO LAN DUSTA (A)
Technical specifications		1.5 TSI/150 kW PHEV (A)
Body		
Body		5 door, two compartment, 5 seater
Drag coefficient c _w		0.269–0.283
Outside dimensions		
Length	[mm]	4902
Width	[mm]	1849
Height (at kerb weight)	[mm]	1483
Wheel base (at kerb weight)	[mm]	2841
Clearance (at kerb weight)	[mm]	140
Track front	[mm]	1584
Track rear	[mm]	1571
Inside dimensions		
Width of front seats	[mm]	1508
Width of rear seats	[mm]	1504
Headroom in front seats	[mm]	1049
Headroom in rear seats	[mm]	1008
Storage capacity	[1]	510
Storage capacity with rear seatback folded down	ניז	1770
Weights		
Kerb weight – incl. driver 75 kg	[kg]	1853–1987
Payload – incl. driver 75 kg	[kg]	438–572
Total weight	[kg]	2350
Max. roof load	[kg]	100
Max. trailer load w/o brakes	[kg]	750
Max. trailer load with brakes – 12%	[kg]	1800
Max. trailer load with brakes – 8%	[kg]	1800
Max. nose weight	[kg]	90
Liquids		
Tank capacity	[1]	45
Battery capacity	[kWh]	25.7

2/3 11. 3. 2024

Superb Combi iV

Petrol engine



Technical specifications		1.5 TSI/150 kW PHEV (A)
Performance/consumption		
Maximum speed	[km/h]	220
Acceleration 0-100 km/h	[s]	8.1
Fuel consumption – combined (WLTP)	[l/100 km]	-
CO ₂ emissions – combined (WLTP)	[g/km]	-
Electric consumption – combined (WLTP)	[kWh/100 km]	-
Pure electric range – combined (WLTP)	[km]	-
AC charging (0–100 %) – power/time (according to the type of cable)		11 kW/2 h 30 min
DC charging (10–80 %) – power/time		40 kW/26 min
Turning circle diameter	[m]	11.1

Technical specifications and drawings apply to the Selection version. The parameters for L&K cars may differ.

3/3

⁻ The data are not available on the press deadline.