Kodiaq Petrol engines



Technical specifications		1.5 TSI/110 kW ACT (A)	
Engine			
Engine type		turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front	
Cylinders		4	
Displacement	[cm ³]	1498	
Bore × Stroke	[mm × mm]	74.5 × 85.9	
Max. engine performance/revs	[kW at rpm]	110/5000–6000	
Max. torque/revs	[Nm at rpm]	250/1500–3500	
Compression ratio		12.0 : 1	
Emission limit		EU 6 EA	
Fuel injection system		electronically controlled direct injection	
Ignition		control unit controlled electronic ignition system	
Lubrication		force-feed lubrication with through-flow oil filter	
Fuel quality		unleaded petrol min. RON 95	
Transmission			
Wheel drive		front wheel drive	
Clutch two coaxial wet multiple-disk clutch, electro-hydraulically operated		two coaxial wet multiple-disk clutch, electro-hydraulically operated	
Transmission automatic 7-speed, DSG, with Tiptronic manual gear changing		automatic 7-speed, DSG, with Tiptronic manual gear changing	
Transmission ratio I-3.190 II-2.750 III-1.897 IV-1.040 V-0.793 VI-0.860 VII-0.661 R-2.900		I-3.190 II-2.750 III-1.897 IV-1.040 V-0.793 VI-0.860 VII-0.661 R-2.900	
Axle ratio		I-5.200 II-3.900	
Chassis			
Front axle		MacPherson suspension with lower triangular links and torsion stabiliser	
Rear axle		multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser	
Springs		telescopic shock absorbers with coil springs, in the rear outside the springs	
Braking system		hydraulic diagonal dual-circuit braking system, electromechanical servo assisted	
Brake – front		disc brakes with inner cooling, with single/piston floating caliper	
Brake – rear		disc brakes	
Parking brake electromechanical, on rear wh		electromechanical, on rear wheels	
Steering system		direct rack and pinion steering with electro mechanic power steering	
Body			
Body		5 door, two compartment, 5 seater {7 seater}	
Drag coefficient c _w		0.281–0.309 {0.293–0.321}	

Kodiaq Petrol engines



Technical specifications		1.5 TSI/110 kW ACT (A)	
Outside dimensions			
Length	[mm]	4758	
Width	[mm]	1864	
Height (at kerb weight)	[mm]	1659 {1658}	
Wheel base	[mm]	2791	
Clearance (at kerb weight)	[mm]	189	
Track front	[mm]	1586	
Track rear	[mm]	1575 {1576}	
Inside dimensions			
Width of front seats	[mm]	1503	
Width of rear seats (2 nd /3 rd row)	[mm]	1492/ {1497/1272}	
Headroom in front seats	[mm]	1063	
Headroom in rear seats (2 nd /3 rd row)	[mm]	1015/- {1015/920}	
Storage capacity (behind 3 rd row of seats up to headrests, boot cover is stored under the boot floor)	[1]	{340}	
Storage capacity up to the rear shelf (with 3^{rd} row of seats folded down, depending on position of backrest, and depending on the position of adjustable 2^{nd} row of seats)	[1]	910 {845}	
Storage capacity with rear seats folded down, up to the roof	[1]	2105 {2035}	
Weights			
Kerb weight – incl. driver 75 kg	[kg]	1661–1819 {1703–1905}	
Payload – incl. driver 75 kg	[kg]	503–689 {525–697}	
Total weight	[kg]	2178–2360 {2231–2424}	
Max. roof load	[kg]	75	
Max. trailer load w/o brakes	[kg]	750	
Max. trailer load with brakes – 12%	[kg]	1800	
Max. trailer load with brakes – 8%	[kg]	1800	
Max. nose weight	[kg]	100	
Liquids			
Tank capacity	[1]	55	

Kodiaq Petrol engines



Technical specifications		1.5 TSI/110 kW ACT (A)
Performance/consumption		
Maximum speed	[km/h]	207 {205}
Acceleration 0–100 km/h	[s]	9.7 {9.9}
Fuel consumption – combined (WLTP)	[l/100 km]	5.9–6.6
CO ₂ emissions – combined (WLTP)	[g/km]	135–151
Turning circle diameter	[m]	11.2

Technical specifications and drawings apply to the Selection version. { } Applies to 7-seater.



Kodiaq Diesel engines



Technical specifications	2.0 TDI/110 kW (A)	2.0 TDI/142 kW 4×4 (A)
Engine		
Engine type	turbocharged diesel engine, turbocharger with self-aligning bl	ades, in-line, liquid cooling system, DOHC, transverse in front
Cylinders		4
Displacement [cm ³]	1968	
Bore × Stroke [mm × mm]	81.0 :	< 95.5
Max. engine performance/revs [kW at rpm]	110/3000–4200	142/3500–4200
Max. torque/revs [Nm at rpm]	360/1600–2750	400/1750–3250
Compression ratio	16.0 : 1	15.5 : 1
Emission limit	EU	δEA
Fuel injection system	electronically controlled high-pressure	direct injection – common-rail system
Lubrication	force-feed lubrication w	ith through-flow oil filter
Fuel quality	die	sel
Transmission		
Wheel drive	front wheel drive	four-wheel drive with automatic torque distribution
Clutch	two coaxial wet multiple-disk clut	ch, electro-hydraulically operated
Transmission	automatic 7-speed, DSG, with Tiptronic manual gear changing	
Transmission ratio	I-3.579 II-2.750 III-1.677 IV-0.889 V-0.677 VI-0.722 VII-0.561 R-2.900	I-3.579 II-2.750 III-1.677 IV-0.889 V-0.677 VI-0.722 VII-0.561 R-2.900
Axle ratio	I-4.813 II-3.667	I-4.813 II-3.667
Chassis		
Front axle	MacPherson suspension with lower	triangular links and torsion stabiliser
Rear axle	multi-element axle, with one longitudinal and	three transverse links, with torsion stabiliser
Springs		prings, in the rear outside the springs
Braking system	hydraulic diagonal dual-circuit braking s	/stem, electromechanical servo assisted
Brake – front	disc brakes with inner cooling, v	vith single/piston floating caliper
Brake – rear	disc b	rakes
Parking brake	electromechanica	al, on rear wheels
Steering system	direct rack and pinion steering wit	n electro mechanic power steering
Body		
Body	5 door, two compartme	ent, 5 seater {7 seater}
Drag coefficient c _w	0.285–0.313 {0.299–0.326}	0.289–0.317 {0.302–0.329}

Kodiaq Diesel engines



Technical specifications		2.0 TDI/110 kW (A)	2.0 TDI/142 kW 4×4 (A)
Outside dimensions			
Length	[mm]	4758	
Width	[mm]	186	54
Height (at kerb weight)	[mm]	1659 {1658}	1657 {1656}
Wheel base	[mm]	275	91
Clearance (at kerb weight)	[mm]	189	187
Track front	[mm]	158	36
Track rear	[mm]	1575 {	1576}
Inside dimensions			
Width of front seats	[mm]	150	03
Width of rear seats (2 nd /3 rd row)	[mm]	1492/- {14	97/1272}
Headroom in front seats	[mm]	106	63
Headroom in rear seats (2 nd /3 rd row)	[mm]	1015/ {1	015/920}
Storage capacity (behind 3 rd row of seats up to headrests, boot cover is stored under the boot floor)	[1]	{340}	
Storage capacity up to the rear shelf (with 3 rd row of seats folded down, depending on position of backrest, and depending on the position of adjustable 2 nd row of seats)	[1]	910 {845}	
Storage capacity with rear seats folded down, up to the roof	[1]	2105 {2035}	
Weights			
Kerb weight – incl. driver 75 kg	[kg]	1730–1933 {1785–1982}	1798–2000 {1853–2049}
Payload – incl. driver 75 kg	[kg]	502-659 {535-712}	465–647 {536–704}
Total weight	[kg]	1730–1933 {1785–1982}	1798–2000 {1853–2049}
Max. roof load	[kg]	75	
Max. trailer load w/o brakes	[kg]	750	
Max. trailer load with brakes – 12%	[kg]	2000	2300 {2400–2500}
Max. trailer load with brakes – 8%	[kg]	2000	2300 {2400–2500}
Max. nose weight	[kg]	100	
Liquids			
Tank capacity	[1]	55	58

Kodiaq Diesel engines



Technical specifications		2.0 TDI/110 kW (A)	2.0 TDI/142 kW 4×4 (A)
Performance/consumption			
Maximum speed	[km/h]	205 {203}	220 {217}
Acceleration 0–100 km/h	[s]	9.6 {9.8}	7.8 {8.0}
Fuel consumption – combined (WLTP)	[l/100 km]	5.3–5.9	6.0–6.6
CO ₂ emissions – combined (WLTP)	[g/km]	138–155	157–174
Turning circle diameter	[m]	11	1.2

Technical specifications and drawings apply to the Selection version. { } Applies to 7-seater.



Kodiaq iV Petrol engine



Technical specifications		1.5 TSI/150 kW PHEV (A)	
Engine			
Engine type		turbocharged petrol engine, in-line, liquid cooling system, DOHC, transverse in front and electromotor	
Cylinders		4	
Displacement	[cm ³]	1498	
Bore × Stroke	[mm × mm]	74.5 × 85.9	
Max. engine performance/revs	[kW at rpm]	110/5000–6000	
Max. torque/revs	[Nm at rpm]	250/1500–4000	
Maximum output of electromotor	[kW]	85	
Maximum torque of electromotor	[Nm]	330	
Maximum system output	[kW]	150	
Maximum system torque	[Nm]	350	
Compression ratio		11.5 : 1	
Emission limit		EU 6 EA	
Fuel injection system		electronically controlled direct injection	
Ignition		control unit controlled electronic ignition system	
Lubrication force-feed lubrication with through-flow oil filter		force-feed lubrication with through-flow oil filter	
Fuel quality		unleaded petrol min. RON 95	
Transmission			
Wheel drive		front wheel drive	
utch three coaxial wet multiple-disk clutch, electro-hydraulically operated			
Transmission automatic 6-speed, DSG, with Tiptronic manual gear changing			
ransmission ratio I-3.500 II-2.773 III-1.852 IV-1.020V-1.023 VI-0.840 R-2.864		I-3.500 II-2.773 III-1.852 IV-1.020V-1.023 VI-0.840 R-2.864	
Axle ratio I-4.588 II-3.545		I-4.588 II-3.545	
Chassis			
Front axle		MacPherson suspension with lower triangular links and torsion stabiliser	
Rear axle		multi-element axle, with one longitudinal and three transverse links, with torsion stabiliser	
Springs		telescopic shock absorbers with coil springs, in the rear outside the springs	
Braking system		hydraulic diagonal dual-circuit braking system, electromechanical servo assisted	
Brake – front		disc brakes with inner cooling, with single/piston floating caliper	
Brake – rear		disc brakes	
Parking brake		electromechanical, on rear wheels	
Steering system		direct rack and pinion steering with electro mechanic power steering	
Body			
Body		5 door, two compartment, 5 seater	
Drag coefficient c _w		0.296–0.324	

Kodiaq iV Petrol engine



Technical specifications	1.5 TSI/150 kW PHEV (A)
Outside dimensions	
Length [mm]	4758
Width [mm]	1864
Height (at kerb weight) [mm]	1656
Wheel base [mm]	2791
Clearance (at kerb weight) [mm]	189
Track front [mm]	1586
Track rear [mm]	1576
Inside dimensions	
Width of front seats [mm]	1503
Width of rear seats [mm]	1492
Headroom in front seats [mm]	1063
Headroom in rear seats [mm]	1015
Storage capacity up to the rear shelf (depending on position of backrest, and depending on the position of adjustable 2 nd [I] row of seats)	745
Storage capacity with rear seats folded [I] down, up to the roof	1945
Weights	
Kerb weight – incl. driver 75 kg [kg]	1913–2084
Payload – incl. driver 75 kg [kg]	423–594
Total weight [kg]	2432
Max. roof load [kg]	75
Max. trailer load w/o brakes [kg]	750
Max. trailer load with brakes – 12% [kg]	1800
Max. trailer load with brakes – 8% [kg]	1800
Max. nose weight [kg]	100
Liquids	
Tank capacity [I]	45
Battery capacity [kWh]	25.7

Kodiaq iV Petrol engine



Technical specifications		1.5 TSI/150 kW PHEV (A)
Performance/consumption		
Maximum speed	[km/h]	210
Acceleration 0–100 km/h	[s]	8.4
Fuel consumption – combined (WLTP)	[l/100 km]	_
CO ₂ emissions – combined (WLTP)	[g/km]	_
Electric consumption – combined (WLTP)	[kWh/100 km]	_
Pure electric range – combined (WLTP)	[km]	_
Turning circle diameter	[m]	11.2

Technical specifications and drawings apply to the Selection version. – The data are not available on the press deadline.